




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>G06F 15/18</b>		A1	(11) International Publication Number: <b>WO 98/06044</b>
			(43) International Publication Date: 12 February 1998 (12.02.98)
(21) International Application Number: PCT/US97/13254 (22) International Filing Date: 29 July 1997 (29.07.97) (30) Priority Data: 08/689,338                  6 August 1996 (06.08.96)                  US (71) Applicant (for all designated States except US): AI WARE, INC. [US/US]; 3659 Green Road, Beachwood, OH 44106 (US). (72) Inventors; and (75) Inventors/Applicants (for US only): PAO, Yoh-Han [US/US]; 2721 Scarborough Road, Cleveland Heights, OH 44106 (US). YIP, Pui-Chiu [CN/US]; Apartment 1607, 24451 Lakeshore Boulevard, Euclid, OH 44123 (US). (74) Agent: GARRED, John, X.; Benesch, Friedlander, Coplan & Aronoff LLP, Suite 200, 2300 BP America Building, Cleveland, OH 44114 (US).		(81) Designated States: AL, AM, AT, AT (Utility model), AU (Petty patent), AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report.          Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	

(54) Title: UNIVERSAL SYSTEM FOR ARTIFICIAL INTELLIGENCE BASED LEARNING, CATEGORIZATION, AND OPTIMIZATION



## (57) Abstract

A parallel, distributed processing system is provided for solving NP-hard problems, and the like, efficiently, quickly and accurately. The system employs parallel processors which are iteratively and intelligently allocated for a series of generations of child solutions from selected, previous generation or parent solutions. The system employs multiple levels of competition for generating a next level of possible solutions and for reallocating processor resources to the most promising regions for finding a best solution to the task. This includes both inter-family competition, as well as intra-family competition. System temperature data are set and gradually decreased with each succeeding generation. A degree of randomness is entered into the solution generation. The hierarchical and iterative process, incorporating randomness and a decreasing temperature provides for the guided evolutionary simulated annealing solution generation.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

**UNIVERSAL SYSTEM FOR ARTIFICIAL INTELLIGENCE  
BASED LEARNING, CATEGORIZATION, AND OPTIMIZATION**

**Related Applications**

The present application is a continuation-in-part of co-pending application serial number 08/271,484 filed July 7, 1994.

**Technical Field**

5        This application pertains to the art of multi-processor computer systems, and more particularly to a multi-processor computer system adapted for efficient solution of extremely complex problems. It will be appreciated that the system has broader applications, such as in the providing of fast or real-  
10       time solutions to problems that are not solvable with conventional computer technology without an inordinate allocation of processor time.

**Background of the Invention**

15       There exists a large number of problems for which no easily discernable solution may be obtained. However, it is accepted that these problems do, in fact, have a solution. Two types of such optimization problems are combinatorial optimization problems and continuous or functional optimization problems.

20       Common examples of combinatorial optimization (also referred to hereinafter as "NP-hard" or "NP-complete"), problems include the "traveling salesman problem," the "four-color map problem," and the like. In the traveling salesman problem, a salesman must visit a number of cities. A scheduling of trips is desirable

which minimizes the total mileage which must be traveled to reach every city. Of course, such a solution exists. However, it may only be found through conventional computation with brute-force calculations.

5           In the four-color map problem a two-dimensional map of political subdivisions is provided. It is desired that a color scheme be affixed such that a different color is assigned for each such subdivision wherein no two adjoining subdivisions are provided with the same color. It has been proven that such a  
10           solution exists. Again, the selection is not apparent and requires massive computations to secure a solution.

          Another such NP-hard problem is the facility layout problem. The task in the facility layout problem is to assign  $n$  facilities to  $n$  locations. A non-negative weight is associated with the  
15           activity between each pair of facilities. It is desired to place each facility in a location that serves to minimize the sum of the weights times distances between pairs of facilities. It is difficult or prohibitive to provide enough conventional computer power to secure a solution by conventional search techniques.

20           In functional optimization problems, the task is to find the location and value of a global minimum (or maximum) for a continuous function defined in a multi-dimensional space. For example, the cost of an item may be a non-linear function of both item size and item weight. The defined function might be  
25           represented as a three dimensional plot having a plurality of local maxima and minima. The slope of the "hills" and "valleys" around the local maxima and minima values can vary considerably,

thereby creating a complicated three dimensional landscape.

Typically, a gradient search technique is applied to find a solution to such a functional optimization problem.

Often times, there is a desire to provide a solution to such  
5 problems in real-time. Early approaches to solving such problems without conventional computing techniques have employed artificial intelligence-based systems. A recurring problem with conventional artificial intelligence approaches is found with "local minimum." Many solution curves provide a solution at  
10 which the first derivative is zero and the second derivative negative. This might appear, at first glance, to provide an overall system minimum and desirable solution. Further investigation often reveals that the function was, in fact, provided at a local minimum. Thus, a better system-wide solution  
15 was available but is not readily discernable.

Different artificial intelligence based systems may more readily lend themselves to finding solutions for one or the other of the two types of optimization problems discussed above. It is desirable to provide a system to efficiently utilize processing  
20 resources to solve both types of optimization problems.

#### Summary of the Invention

The present invention contemplates a new and improved computing system which overcomes the above-referred problems, and others, and provides an artificial intelligence based system for  
25 efficient use of processor resources to quickly and accurately

provide best solutions for combinatorial optimization problems and functional optimization problems.

In accordance with the present invention, there is provided a parallel, distributed processing system for problem solutions  
5 employing what is referred to as guided evolutionary simulated annealing ("GESA"). The system includes a plurality of processor units, each of which includes its own local memory. "Parent" or early generation solutions are provided to each of N of the plurality of processors. Each processor is provided with initial  
10 "temperature" data. The individual processors generate "child" or later generation solutions from the parents assigned thereto. A competition is undertaken between the child solutions to determine the best child. The best child competes with the parent of its family to determine the parent of the next  
15 generation. The victors of this competition form the parents for a next iteration. It is possible for the best child to become the parent of the next generation even if it is not better than its parent.

A competition is undertaken among the families to determine  
20 the number of children to be allocated to each family in the next iteration. All of the children of a family are evaluated relative to the current best global solution to determine the fitness of the family. The number of children allocated to each family for the next iteration is based on the family's fitness.  
25 After each iteration of generating a next generation of parents, the temperature coefficients are decreased. Further, at this time a test of possible solutions is made against preselected

acceptability standards. Also, a preset number of maximum iterations is provided. The results of these later two tests selectively allow for problem termination.

5 In accordance with yet another aspect of the present invention, a method is provided for implementing the guided evolutionary simulated annealing noted above.

In accordance with a further aspect of the present invention, a specified hardware platform adapted to accomplish the afore-mentioned guided evolutionary simulated annealing  
10 extremely quickly or in real-time is provided.

An advantage of the subject invention is the provision of a system which facilitates efficient use of processor resources for rapid and accurate isolation of a best solution of NP-hard problems.

15 Yet another advantage in the present invention is the provision of a solution for NP-hard problems which uses relatively inexpensive hardware.

Yet another advantage of the present invention is the provision of a solution for NP-hard problems which may be readily  
20 and easily adapted to a large variety of such problems.

Further advantages will be apparent to one of ordinary skill in the art upon reading and understanding of the subject specification.

#### **Brief Description of the Drawings**

25 The invention may take physical form in certain parts, and arrangements of parts, a preferred embodiment of which will be

described in detail in this specification and illustrated in the accompanying drawings which form a part hereof and wherein:

FIG. 1 illustrates, in block diagram form, a hardware, multi-processor platform to realize the guided evolutionary simulated annealing solution;

FIG. 2 illustrates a state diagram of the hardware architecture of FIG. 1 in connection with the subject invention;

FIG. 3 illustrates, in flow chart form, the activities of the overall system in connection with guided evolutionary simulated annealing solutions;

FIG. 4 illustrates, in flow chart form, activities for intra-family solution competition; and

FIG. 5 illustrates, in flow chart form, activities for inter-family solution competition.

#### Detailed Description of the Preferred Embodiment

Referring now to the drawings wherein the showings are for the purpose of illustrating the preferred embodiment of the invention only, and not for the purpose of limiting the same, FIG. 1 illustrates a multi-processor platform A suited for accomplishing parallel, distributed processing for achieving problem solutions employing guided evolutionary simulated annealing. The multiprocessor platform A includes a plurality of evaluation processors 10i, 10ii, ... 10n. Each evaluation processor is provided with its own local memory or RAM 12i, 12ii, ... 12n, respectively.



Each evaluation processor/local RAM pair 10, 12 provides a mechanism by which the processor may run with a local program and using localized data. Each evaluation processor is also in contact with a dual port memory 14 for data transfer with the control processor. The RAM/evaluation complex is selectively isolated from an associated address bus and data bus by tri-state buffers 14a and 14b. One of the dual data port of the dual port memory 14 is enabled and the other port 13 is disabled by a bus allocation control 20. The bus allocation control 20 keeps track of the system state that defines the control of the dual port memory.

The control processor 28 may suitably run under instructions and data provided in dual port memory 14. Alternatively, the control processor 28 may also be provided with its own local RAM such as local RAM 12 associated with each evaluation processor 10.

The architecture of FIG. 1 allows for highly efficient concurrently processing of intra-family solution possibilities, as well as inter-family solution possibilities in connection with the subject guided evolutionary simulated annealing system disclosed herein. This allows for an efficient and quick determination of an acceptable solution, which may be even accomplished in real-time. The particular processes as run in connection with the multi-processor platform of A of FIG. 1 will be detailed below.

In the architecture of FIG. 1, both the control processor 28, as well as the evaluation processors 10 can have control of

the dual-port memory 14. When the control processor 28 is in control of the memory and the data bus, the evaluation processors are precluded from accessing the memory until control released. Similarly, when the evaluation control processors 12 are in  
5 control of the dual port memory 14, the control processor cannot access the memory until released. The control state of the memory is determined by the current system state, as will be described below.

The bus allocation control 20 serves to keep track of a  
10 current state of the system. In the preferred embodiment, a register (not shown) disposed within the bus allocation control 20 keeps track of a current system state. The control processor 28 updates the system state when the evaluation processors 10 or the control processor 28 signals completion of a current task.  
15 Both the control processor 28 and the evaluation processors 10 can access the register within the bus allocation control 20 to update a current machine state. Thus, all processors are informed when they are able to proceed to a next task in the series thereof which will be detailed below.

20 As noted above, each evaluation processor 10 is provided with its corresponding local RAM 12 in the preferred embodiment. The local memory of each evaluation processor is not shared by other evaluation processors. However, local memory may be accessed by the control processor 28 so it can load some of the  
25 parameters, data, or functions, or the like. Basically, each evaluation processor 10 performs a task specific to a function in its respective local memory.

The control processor 28 functions to allocate and distribute sub-tasks to each evaluation processor 10, via its corresponding local RAM 12. The control processor 28 may suitably pass parameters to each evaluation processor via dual port memory 14. Alternatively, the information may be passed directly to the individual evaluation processors local memory.

During implementation of the GESA system, detailed below, the control processor 28 receives the statement of the task, determines parent solutions and assigns parent solutions for each evaluation processor 10 for each iteration, determines a best result obtained up to a current iteration, determines whether a new iteration is required, and determines the number of children to be allocated to each family in each iteration.

The evaluation processors 10 each determine the objective value for the parent solutions assigned to it, generate children solutions from the parents, determine the objective values for the children, determine whether a child is accepted and, determines an acceptance number of each family represented therein.

The dual port memory 14 serves as a communication interface for the control processor 28 and the evaluation processors 10. Both the control processor 28 and the evaluation processor 10 can access the dual port memory 14. However, control is determined by a current system state as noted above.

The operation of the subject hardware platform may suitably be thought in terms of five different operation states. operation of each module within the multi-processor platform A is

determined by a current state of the system. The following state description is provided in FIG. 2.

#### State 1

State 1 provides an entry point from the GESA algorithm.  
5 The system goes to this state when the GESA algorithm is called by another part of the complete program. A goal function is passed to the control processor, at which point the system passed to state 2.

#### State 2

10 When in state 2, the control processor 28 is in full control of the dual port memory 14. It loads an evaluation function, parameters and data into memory so that the evaluation processors 10 can use them in later states. Additionally, the control processor 28 generates *N* solution candidates randomly. These  
15 solution candidates are called parent solutions or parents. The control processor 28 replicates *M* copies for each Parent, and stores the copies into the local memory 12 for each evaluation processor.

When in state 2, the evaluation processors 10 continue  
20 reading the system state, as provided in bus allocation control 20, until proceeding to state 3 as detailed below. The control processor 28 releases the bus by giving a signal to the bus allocation control 20. At this point, the system state is incremented by one, i.e., to state 3.

State 3

While in state 3, the control processor 28 continues reading the system state until the system progresses to state 4. Each evaluation processor receives a parent, provides a mutation to generate a child solution or child therefrom. It evaluates and returns an objective value and an acceptance status of that child. Each evaluation processor signals the bus allocation controller 20 when it has finished its evaluation. The bus allocation controller 20, in turn, increments the system state by one after all evaluation processors 10 have signalled to indicate completion of their respective evaluations. This causes progress to state 4.

State 4

While in state 4, the control processor 28 determines a parent of a next generation solution and an acceptance number from each family. It then computes a number of child processes or children that should be generated in the subsequent generation, for each parent. Replica of the parents according to that number are generated and stored in a respective local memory 12 for each evaluation processor. The control processor 28 also determines a lowest objective value. It stores that lowest objective value in the local memory 12 associated with each evaluation processor 10. Thus, each evaluation processor may determine its own acceptance.

This evaluation continues by reading the system state until it progresses to state 5. The control processor 28 signals the

bus allocation controller after it has finished a task for a current state. At this point, the state is incremented by one to state 5.

#### State 5

5        While in state 5, the control processor 28 checks termination criteria. A positive determination, based on this check, results in the return of a solution with a lowest objective value, to a user program. Otherwise, the control processor changes the system back to state 3 and progress  
10        therefrom.

#### Implementation of Guided Evolutionary Simulated Annealing

Referring now to FIGS. 3-5, the control process of the present invention will be better appreciated. The GESA search technique starts out with a guess of  $N$  likely solution  
15        candidates. In the preferred embodiment, these candidates are chosen at random from the solution search space. These candidates are the parent solution or so-called parents. Initially, each parent generates the same number of children, for example,  $M_1$ .

20        As noted above, the GESA system provides two levels of competition. In a local competition the children in the family (i.e., generated from the same parent), compete with one another and only the child with the lowest objective value survives. This best child then competes with its own parent to determine  
25        which should survive to become the parent for the next iteration.

If the best child is better than its parent, then it is accepted as a parent for the next generation. If the best child is worse than his parent, there is a Boltzmann probability that the child will be accepted. In the preferred embodiment, the best child is  
 5 accepted as a parent for a subsequent generation if:

$$Y_c < Y_p$$

or if,

$$\exp\left[\frac{-(Y_c - Y_p)}{t_c}\right] > p$$

10

wherein,

$Y_c$  = an objective value of a best child solution,  
 $Y_p$  = an objective value of a parent solutions,  
 associated with the best child solution,  
 15  $p$  = a random number randomly distributed between 0 and 1, and  
 $t_c$  = a temperature coefficient.

This forms the local competition to create parents for a next generation.

20 The second level of competition is competition among families. A number of children to be generated for each family in a next generation depends on a result of such second level competition. A measure of fitness is calculated for each family to be used in the second level competition.

25 A typical measure might be against an objective value of a single point. However, such a measure may be biased. Instead, in the present invention, all children are used for such a measure. Each child has an objective value that is compared to a lowest objective value ever found for all solution candidates in  
 30 an entire evolution process. That is to say, an objective value

of a child is compared to a lowest objective value found in the entire population, up to the previous generation. If the child is better than the lowest objective value, then it is accepted and the family count is incremented. Family count is also  
 5 referred to as family acceptance number which is a measure of family fitness compared relative to the other families. If the objective value of the child is worse than the lowest object value, there is a Boltzmann probability that the child will be accepted and the family count incremented. In the preferred  
 10 embodiment, the child is accepted and the family count incremented if:

$$Y_i < Y_{\min}$$

as described above, or if,

$$\exp\left\{\frac{-(Y_i - Y_{\min})}{t_i}\right\} > p$$

wherein,

20  $Y_i$  = an objective value of a child solution,  
 $Y_{\min}$  = a lowest objective value of solutions found in the entire population, up to the previous generation,  $p$  = a random number randomly distributed between 0 and 1, and  
 $t_i$  = a temperature coefficient.

The total number of children  $T$  generated in each generation  
 25 is due to fixed hardware considerations. In a massively parallel machine, a number of processing elements is fixed. Insofar as each individual in the population is handled by a processing element, such as the evaluation processors 10 of FIG. 1, the dimension on the population should be fixed.

30

$$T = \sum_{i=1}^N m_i$$



1-1

A number of children from the next generation for each family is chosen to be proportional to the acceptance number for the family such that:

$$M' = \frac{T \times A}{S}$$

5        wherein,

        M' = the number of children that will be generated for that family,

        T = the total number of available children for all families, e.g. MxN children,

10        A = the acceptance number for that family, and

        S = the sum of the acceptance numbers, i.e. counts, for all families.

thus, there remains a constant total number of children T to be reallocated among the families according to family fitness as  
15        indicated by the family acceptance number.

        The afore-noted procedure continues until a preselected number of iterations have been reached, or until such time as an acceptable solution has been found. The second level competition has an effect of giving a measure of regional information. The  
20        acceptance number provides information as to how good a region is. If a region is believed to have a better likelihood of obtaining an optimal solution (as measured by a higher acceptance number), the search focuses more intently on this region.

        In a preferred embodiment, each of (i) the local  
25        competition, (ii) the global competition, and (iii) the children generation functions have a temperature value. The system starts with a higher initial temperature value for each. These

temperature values are decreased after each generation until each reaches a "freezing temperature," at which time the temperature stops decreasing. A preferred method of varying each of the temperature values is expressed as:

5

$$t_{\text{new}} = c \times t_{\text{old}}$$

wherein,  $c$  is a constant less than 1.

The foregoing system may also be viewed as parallel simulated annealing with competition. Each family may be thought of as a multiple-trial-parallel simulated annealing machine, with the children contributing trials in parallel. In the GESA implementation we have  $N$  parallel simulated annealing machines. These  $N$  machines compete with one another. The better solution will have more trials and the worst will have fewer trials. The number of trials should be increased with a decreasing temperature level. The inter-family competition (second level or global competition), provides such a mechanism. A number of trials for a best parallel simulated annealing machine (that is the number of children generated from the best family), increases with decreasing temperature or increasing iterations.

15

20

Turning particularly to FIG. 3, the general control process of the present invention will be better appreciated. The flow chart details the overall GESA process. The system is commenced at block 100. At block 102, the control processor 28 receives (i) the statement of the task, (ii) the names of variables, (iii) the ranges for the variables, (iv) the objective function, and the values for search parameters, e.g. initial temperature value are set for all three temperature values  $t_1$ ,  $t_2$ , and  $t_3$ . The

25

number  $N$  of families is specified as well as the total number of children  $T=M \times N$  where  $M$  is the number of children allocated to each family  $N$  for the first iteration. The system then progresses to block 104.

5           In block 104, the  $N$  initial parent solutions are selected randomly by the control processor. The control processor posts the description of each of the parents and assigns the initial  $N$  parents to  $N$  evaluation processors. The control processor then initially assigns  $M$  children to each  $N$  parents, thereby forming  
10 families. The children are given ID's to indicate parent or family affiliation. A particular child will remain at the same processor throughout all of the subsequent iterations regardless of new family allocations. Further, some processors may be reserved for processing children only thereby having a total  
15 number of processors in excess of  $N$ . The allocation of children described above among the processors results in efficient utilization of processor resources regardless of the increased size of a particular family due to reallocation of children based on family fitness. Also in block 104, the evaluation processors  
20 evaluate the objective function for each parent allocated to the evaluation processor. The objective value for each parent solution is returned to the control processor. The control processor then orders the objective values for all of the parent solutions and posts, i.e. saves, the lowest parent objective  
25 value as the initial global minimum objective value  $Y_{gl}$ .

Next, in block 106, the evaluation processors generate children or child solutions from their parents or parent

solutions. A simple mutation of a randomly selected element in a parent solution is used to generate a child. Preferably, the random change is proportional to  $t_j$ .

5 In block 108, the first level (intra-family or local competition) is undertaken to determine which parents will be used for a next generation. The competition is amongst the children to determine the best child in a family. Then, the best child competes against its parent to become the next generation parent.

10 Referring to Fig. 4, the process for selecting the next generation parents will be better appreciated. The process begins at block 160. Next, in block 161, a family is selected which has yet to have the next generation parent determined. In block 162, the evaluation processors determine the objective  
15 value for each of the children in the selected family. Next, in block 164, the evaluation processors find the best child, i.e. the lowest objective value, from each family represented in an evaluation processor. The best children from the families are returned, with their family ID's, to the control processor to  
20 compete with their respective parents. In block 166, the competition between the best child and its parent begins where a determination is made as to whether the objective value of the best child in a family is better than the objective value of its parent. If the determination in block 166 is affirmative, the  
25 process proceeds to block 168 where the best child is accepted as the parent for the next generation. If the determination in block 166 is negative, indicating that best child is worse than

its parent, the process proceeds to block 172. In block 172, there is a determination as to whether the best child satisfies the Boltzmann probability criterion as described above. If the determination in block 172 is affirmative, the process proceeds to block 168 where the child is selected as the next generation parent. From block 168 the process then proceeds to step 170 where a determination is made as to whether all of the parents for the next generation have been selected. If all the families have been evaluated and all next generation parents are selected, the process proceeds to step 172 where the first level competition procedure is ended. If the determination in step 170 is negative indicating that additional families have yet to determine the next generation parent, the process returns to block 161. In block 161, a next family, yet to be addressed, is selected and the process continues as described above to evaluate the newly selected best child and parent.

If the Boltzmann probability criterion determination in block 172 is negative, indicating that the parent is the victor of the competition, the process continues on to block 174 where the parent is accepted as the parent for the next generation. From block 174 the process advances to block 170 and the remainder of the process continues as described above.

For each family, the control processor specifies and posts the ID for the parents of the next generation. The control processor compares all of the objective values and determines the new global minimum objective value  $Y_{GL}$ . The new global objective value is then posted by the control processor for use by the

evaluation processors. Once all of the families have completed the first level competition, and all of the next generation parents have been selected and posted, the process then returns to the overall control process shown in Fig. 3.

5 Referring again to Fig. 3, the process continues to block 110 where a test is made against preselected criteria to determine whether an acceptable solution has been found. A positive determination results in an end or completion of the procedure at block 112. A negative determination causes an  
10 inquiry at block 114. This inquiry determines whether a preset number of iterations have been completed. Again, a positive determination results in an end of the procedure at block 112. A negative determination causes the process to advance to block 116. At block 116, the temperature coefficients  $t_1$ ,  $t_2$ , and  $t_3$ ,  
15 are decreased as described above.

Next, a detailing of the procedure associated with the second level or inter-family competition, as provided at block 118 of FIG. 3, will be described with FIG. 5.

The inter-family global competition commences at block 200.  
20 In block 210, the evaluation processors set a value COUNT equal to zero for the families represented therein. At step 210, a next family, which has yet to be addressed, is selected. The selected family is then dealt with commencing at block 214. At this point, a child which has yet to be dealt with, is selected.  
25 At block 216, the objective value of that child is tested to determine whether it is lower than the lowest global minimum objective value  $Y_{GL}$ . A negative determination causes progress to

block 218, at which point the above-noted equation is tested. A positive determination at block 216 causes progress to block 220.

At this point, the value COUNT for the family is incremented.

Returning back to block 218, a positive determination  
5 results in progress to block 220, as described above. The output  
of block 220, as well as a negative determination resultant from  
block 218, causes progress to block 222. At this point, a  
determination is made as to whether all children within the  
particular family have been addressed. If not, the next child is  
10 selected back in block 214. If so, progress is made to block  
224.

In block 224, an acceptance number of the particular family  
is set equal to the value COUNT. The evaluation processors  
determine the acceptance numbers for all of the families  
15 represented therein and returns the acceptance numbers to the  
control processor. In step 226, each evaluation processor  
determines whether all of the families represented therein have  
been evaluated. If the determination is negative, the process  
returns to block 212. If the determination in block 226 is  
20 affirmative, indicating that evaluation of all of the families is  
completed, the process continues to block 228. At this point,  
all families have been dealt with and have been provided with an  
acceptance number. Block 228 sums the acceptance number of all  
such families. Next, at block 230, a calculation, as described  
25 above, is made as to the number of children to be generated in  
the next generation. The routine ends at 232, at which point  
progress would be made back to block 112 of FIG. 3.

The GESA system detailed above has been applied to several NP-complete problems. In each instance, the GESA approach has been found to provide a quick and accurate means of solving such problems. It will be appreciated by one skilled in the art that the GESA system (i) is an efficient guided optimization technique that reallocates processor resources to focus the solution task in the most promising solution areas, (ii) efficiently distributes the processing tasks among the processors, (iii) has the capability to escape from local minima, and (iv) has the ability to converge to a solution with arbitrary accuracy. The GESA algorithm is free of the constraints of linear representation imposed by using binary strings and does not require pairing in generating new child solutions.

This invention has been described with reference to the preferred embodiment. obviously, modifications and alterations will occur to others upon a reading and understanding of the specification. It is intended that all such modifications and alternations be included insofar as they come within the scope of the appended claims or the equivalents thereof.



Having thus described the invention, it is now claimed:

1. A parallel, distributed processing system for problem solutions employing guided evolutionary simulated annealing comprising:

- an iteration data storage for storing data  
5 representative of a preselected number of iterations;
  - means for storing an integer  $N$  representative of a number of randomly generated parent solutions;
  - means for allocating an integer  $M$  representative of a number of children solutions to each of the  $N$  parent solutions;
  - 10 means for allocating  ~~$M$~~  $N$  children solutions among each of an integer  $P$  representative of a plurality of processor units;
  - means for enabling the plurality  $P$  of processor units, each processor unit including,
    - means for receiving data representative of  
15 one of the  $N$  parent solutions,
    - generating means for generating child solutions from the received one of the  $N$  parent solutions, the parent solution and all child solutions generated from the parent solution  
20 forming a family,
    - global comparison means for comparing each child solution generated by the generating means against a preselected global criterium, and
    - pruning means for selecting a subset  $N'$  of  
25 child solutions generated by the generating means

in accordance an output of a local comparison means for comparing each child solution generated by the generating means against a preselected local criterium, the subset of  $N'$  child solutions  
30 forms a next generation of parent solutions;

means for re-allocating the ~~MDN~~ number of children solutions among each of the  $N'$  parent solutions in response to the global comparison means; and

means for iteratively communicating  $N'$  child solutions as a next generation of  $N$  parent process to the plurality  $P$  of processor units until reaching at least one of (i) the preselected number of iterations in accordance with a comparison of the data representative of a preselected number of iterations stored in the iteration data storage and (ii) achievement of an acceptable solution from the previous child solution subset.

2. The parallel, distributed processing system for problem solutions employing guided evolutionary simulated annealing of claim 1 further comprising:

5 a temperature data storage for storing temperature data representative of an initial temperature  $t$ ;

means for decreasing a value of the temperature data during each iteration of the preselected number of iterations; and wherein the pruning means includes means for selecting the subset of child solutions in accordance with the temperature  
10 data.

3. The parallel, distributed processing system for problem solutions employing guided evolutionary simulated annealing of claim 2 further comprising:

means for computing an objective value  $y_p$  of a parent solution in the family;

means for computing an objective value  $y_c$  of each child solution in the family;

means for storing a value representative of a lowest objective value associated with child solutions in the family;

testing means for testing the lowest objective value associated with the child solutions against the objective value of the parent of the family; and

wherein the pruning means further includes means for selecting the subset of child solutions in accordance with an output of the testing means.

4. The parallel, distributed processing system for problem solutions employing guided evolutionary simulated annealing of claim 3 wherein the testing means tests the child solutions against the local criterion in accordance with at least one of the relation,

or,

$$\exp\left[\frac{-(y_c - y_p)}{t_i}\right] > p$$

wherein,

$y_c$  = an objective value of a best child solution,  
 $y_p$  = an objective value of a parent solutions,  
 associated with the best child solution,

$p$  = a random number randomly distributed between 0 and 1, and

$t_i$  = a temperature coefficient.

5. The parallel, distributed processing system for problem solutions employing guided evolutionary simulated annealing of claim 3 wherein the global comparison means includes means for incrementing a count value in response to the  
5 preselected global criteria.

6. The parallel, distributed processing system for problem solutions employing guided evolutionary simulated annealing of claim 5 wherein the preselected global criteria are in accordance with at least one of the relation,  
5

$$Y_i < Y_a$$

or,

$$\exp\left[\frac{-(Y_i - Y_a)}{t_i}\right] > p$$

10 wherein,

$Y_i$  = an objective value of a child solution,  
 $Y_a$  = a lowest objective value of solutions found in the entire population, up to the previous generation,  
 $p$  = a random number randomly distributed between 0 and 1, and  
 $t_i$  = a temperature coefficient.  
 15

$$M' = \frac{T \times A}{S}$$

7. The parallel, distributed processing system for problem solutions employing guided evolutionary simulated annealing of claim 6 wherein the means for reallocating the  $M \times N$  number of children among each of the  $N'$  parents is in accordance  
5 with,

wherein,

- 10           M' = the number of children to be allocated to that family,  
            T = the total number of children available for all families, i.e.  $N \times M$ ,  
            A = the count value in response to the global criteria for the family, and  
            S = the sum of all count values for all families during an iteration.

5           8.    The parallel, distributed processing system for problem solutions employing guided evolutionary simulated annealing of claim 7 further comprising means for incrementing a count value for each of the plurality of processor units each time the plurality of N processors are enabled.

            9.    A method of parallel and distributed processing for problem solutions employing guided evolutionary simulated annealing comprising the steps of:

5               storing data representative of a preselected number of iterations;

                  storing an integer N representative of a number of randomly generated parent solutions;

                  simultaneously enabling N of a plurality of processor units;

10               receiving, in each processor unit, data representative of one of the N parent solutions;

                  allocating M child solutions to each one of the N parent solutions forming families;

15               allocating the  $M \times N$  children solutions among the plurality of processor units;

generating, in each processor unit, child solutions from the one of the  $N$  parent solutions;

comparing, in each processor unit, each child solution generated in the generating step against a preselected global  
20 criterium;

determining the fitness of each family in response to the comparison of children of a family against the preselected global criterium;

pruning so as to select a subset of  $N'$  child solutions  
25 generated by the step of generating in accordance an output of a step of locally comparing the children of a family against preselected local criterium, the subset of child solutions forms a next generation of parent solutions;

reallocating the  $M \times N$  number of children solutions among  
30 each of the  $N'$  parent solutions in response to the fitness determination; and

iteratively communicating  $N'$  child solutions as a next generation of  $N$  parent process to the plurality of processor units until reaching at least one of (i) the preselected number  
35 of iterations in accordance with a comparison of the data representative of a preselected number of iterations stored in the iteration data storage and (ii) achievement of an acceptable solution from the previous child solution subset.

10. The method of parallel and distributed processing for problem solutions employing guided evolutionary simulated annealing of claim 9 further comprising the steps of:

computing an objective value  $y_p$  of a parent solution in  
5 the family;  
computing an objective value  $y_c$  of each child solution  
in the family;  
storing a value representative of a lowest objective  
value associated with child solutions in the family;  
10 testing the objective value of the lowest objective  
value associated with child solutions against the objective value  
of the parent of the family; and  
wherein the step of pruning further includes selecting  
the subset of child solutions in accordance with an output of the  
15 step of testing.

11. The method of parallel and distributed processing  
for problem solutions employing guided evolutionary simulated  
annealing of claim 10 further comprising the steps of:

storing temperature data representative of an  
5 initial temperature  $t$ ;  
decreasing a value of the temperature data during  
each iteration of the preselected number of iterations; and  
selecting the subset of child solutions in  
accordance with the temperature data.

12. The method of parallel and distributed processing  
for problem solutions employing guided evolutionary simulated  
annealing of claim 11 wherein the step of determining the fitness

of the families includes incrementing a count value in response  
 5 to the comparison against the preselected global criteria.

13. The method of parallel and distributed processing  
 for problem solutions employing guided evolutionary simulated  
 annealing of claim 12 further comprising the step of incrementing  
 a count value for each of the plurality of processor units each  
 5 time the plurality of N processors are enabled.

14. The method of parallel and distributed processing  
 for problem solutions employing guided evolutionary simulated  
 annealing of claim 10 wherein the step of testing further  
 includes the step of completing a local comparison in accordance  
 5 with at least one of the relation,

$$Y_c < Y_p$$

or,

$$10 \quad \exp\left[\frac{-(Y_c - Y_p)}{t_1}\right] > p$$

wherein,

15  $Y_c$  = an objective value of a best child solution,  
 $Y_p$  = an objective value of a parent solutions  
 associated with the best child solution,  
 $p$  = a random number randomly distributed between 0 and  
 1, and  
 $t_1$  = a temperature coefficient.

15. A parallel processor system for parallel,  
 distributed processing system for problem solutions employing  
 guided evolutionary simulated annealing comprising:



a plurality of evaluation processors;

5 a local memory associated with each evaluation processor, each local memory including,

means for storing data representative of one of  $N$  parent solutions,

means for storing a count value

10 representatives of number of iterations of calculations therethrough, and

means for storing data representative of a lowest acceptable objective value;

a common memory selectively in data communication

15 with each of the evaluation processors, the common memory including,

means for storing data representative of a preselected number of iterations,

means for storing an integer  $N$

20 representative of a number of randomly generated parent solutions,

temperature data storage for storing temperature data representative of an initial temperature  $t$ , and

25 means for storing data representative of an acceptable solution of a given problem;

each evaluation processor including,

means for receiving data representative of one of the  $N$  parent solutions,

30

means for allocating an integer  $M$   
representative of a number of children  
solutions to each of the  $N$  parent solutions;

35

means for allocating the  $M \times N$  children  
solutions among the plurality of evaluation  
processors;

generating means for generating child  
solutions from the one of the  $N$  parent  
solutions,

40

global comparison means for comparing  
each child solution against a pres global  
criterion;

45

local comparison means for comparing  
each child solution generated by the  
generating means against the objective value  
of its parent, and

50

pruning means for selecting a subset of  
 $N'$  child solutions generated by the  
generating means in accordance an output of  
the local comparison means, the subset of  $N'$   
child solutions forms a next generation of  
parent solutions; and

means for re-allocating the  $M \times N$  number of children  
solutions among each of the  $N'$  parent solutions in response to  
the global comparison means.

16. The parallel, distributed processing system for problem solutions employing guided evolutionary simulated annealing of claim 15 wherein the preselected global criteria are in accordance with at least one of the relation,

5 
$$Y_c < Y_a$$

or,

$$\exp\left[\frac{-(Y_c - Y_a)}{t_c}\right] > p$$

10 wherein,

$Y_c$  = an objective value of a child solution,  
 $Y_a$  = a lowest objective value of solutions found in the entire population, up to the previous generation,  
15  $p$  = a random number randomly distributed between 0 and 1, and  
 $t_c$  = a temperature coefficient.

17. The parallel processor system for parallel, distributed processing system for problem solutions employing guided evolutionary simulated annealing of claim 15 further comprising bus allocation control means to coordinate transfers  
5 between each local memory and the common memory.

18. The parallel processor system for parallel, distributed processing system for problem solutions employing guided evolutionary simulated annealing of claim 17 further comprising a control processor in data communication with the bus  
5 allocation control means and the system memory for allocating each next generation of parent solutions to a subset of the evaluation processors.

19. The parallel processor system for parallel,  
distributed processing system for problem solutions employing  
guided evolutionary simulated annealing of claim 18 wherein the  
common memory is comprised of dual port memory facilitating  
5 concurrent access of a plurality of processors to data disposed  
therein.

20. The parallel processor system for parallel,  
distributed processing system for problem solutions employing  
guided evolutionary simulated annealing of claim 19 wherein the  
control processor includes its own local memory for storing local  
5 data and instructions therefor.




Fig. 1

2/5




Fig. 2

3/5




Fig. 3




Fig. 4



5/5




Fig. 5

# INTERNATIONAL SEARCH REPORT

Intern. Application No  
PCT/US 97/13254

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 6 G06F15/18

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 6 G06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	YIP P P C ET AL: "A GUIDED EVOLUTIONARY SIMULATED ANNEALING APPROACH TO THE QUADRATIC ASSIGNMENT PROBLEM" IEEE TRANSACTIONS ON SYSTEMS, MAN AND CYBERNETICS, vol. 24, no. 9, 1 September 1994, pages 1383-1387, XP000462410 see the whole document	1-14
Y	---	15-20
Y	W0 93 25969 A (KOZA JOHN R) 23 December 1993 see page 100, line 1 - page 102, line 19; figure 19 ---	15-20
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

13 November 1997

Date of mailing of the international search report

01.12.97

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Schenkels, P

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 97/13254

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	YIP P P ET AL: "COMBINATORIAL OPTIMIZATION WITH USE OF GUIDED EVOLUTIONARY SIMULATED ANNEALING" IEEE TRANSACTIONS ON NEURAL NETWORKS, vol. 6, no. 2, 1 February 1995, pages 290-295, XP000492663 see the whole document ---	1-20
A	MAHFOUD S W ET AL: "PARALLEL RECOMBINATIVE SIMULATED ANNEALING: A GENETIC ALGORITHM" PARALLEL COMPUTING, vol. 21, no. 1, 1 January 1995, pages 1-28, XP000499056 see page 9, line 26 - page 11, line 5 ---	1,9,15
A	SPIESSENS P ET AL: "A MASSIVELY PARALLEL GENETIC ALGORITHM IMPLEMENTATION AND FIRST ANALYSIS" PROCEEDINGS OF THE INTERNATIONAL CONFERENCE ON GENETIC ALGORITHMS, SAN DIEGO, JULY 13 - 16, 1991, no. CONF. 4, 13 July 1991, BELEW R K;BOOKER L B, pages 279-285, XP000260115 see page 280, left-hand column, line 19 - right-hand column, line 14 -----	1,9,15

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 97/13254

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9325969 A	23-12-93	US 5390282 A	14-02-95
		AU 3928293 A	04-01-94
-----			